

DATASHEET

CATEGORY: APLIWELD®-E
NAME: Apliweld-E: Ignition kit
REFERENCE: AT-100N UK

PRODUCT DESCRIPTION

Kit Apliweld-E: Ignition box enables controlled and remote electronic ignition in a quick and safe way. Includes: ignition unit (AT-096N), cable (AT-098N), 5 crocodile clips (AT-099N), battery charger and transporting bag.



APLIWELD®-E enables controlled and remote electronic ignition in a quick and safe way.

DATASHEET

Reference	AT-100N UK
Dimensions	216 x 180 x 102 mm
Weight	2820 g
Battery life	More than 250 welds from full charge
Includes	Ignition unit (AT-096N), cable (AT-098N), 5 crocodile clips (AT-099N), UK type G plu battery charger and transport carry case
Power supply	Lead-acid battery 12V 2.3Ah
Operating voltage	12 VDC
Charge	12-24 VDC 500 mA
Charge time	6 hours
Cable dimensions	2 x 1.5 x 1500 mm
Work temperature	-10°C to 60°C

INSTRUCTIONS

> INSTALLATION

Insert the pair of pin connectors into the ignition unit. Pin position is indifferent.
 Press both ignition buttons at the same time. Hold down until the reaction initiates.
 It can also be activated with the bluetooth remote (AT-115N).

> SAFETY AND MAINTENANCE

Read carefully the particular product instructions supplied in all Apliweld® products before its use.

All personnel that will carry out Apliweld exothermic welding should be duly trained in the correct usage of the product.

OTHER INFORMATION


> ACCESSORIES



AT-114N
Ignition Unit Apliweld®-E



AT-099N
Clamps renewal (5 units)



AT-101N
Battery charger



AT-115N
Wireless remote control

> RELATED PRODUCTS



AT-020N
Apliweld-T: Welding tablets (20u)



AT-010N
Apliweld-E: Electronic starter (10ud)