

Product Data Sheet



Product Code	Issue Number	Issue Date	Issue Reference
	1	24/07/21	MET01

Product Description

uPVC HEAVY GAUGE ROUND CONDUIT

Features

Full range of accessories to compliment including bends, couplers, inspection elbows and tees, boxes, moulded finishes and more.

Moulded accessory options.



Compliance	BS 4607 Part 5, BSEN 50086-2-1, BSEN 61386-21 (formerly BS 6099)
Material	uPVC – Flame Retardant
Finish	White (Standard)
Supplied Length	4 Metres
Diameter	25mm

Thermal Properties

Centaur uPVC trunking systems are designed to accommodate local thermal expansion and contraction. The coefficient of linear expansion: $7.0 \times 10^{-5} \text{C to } 60^{\circ}\text{C}$.

Environmental Information	<p>Packaging Waste: Outer Bag – 0.0023Kg /LDPE</p> <p>RoHS Compliant ref: 2011/65/EU</p> <p>uPVC Products are insoluble in water and will not degrade when buried in landfills etc. The products manufactured and otherwise supplied by the company do not have any perceived or known hazardous materials or by-products that would be deemed hazardous to the environment.</p>
Hazards Identification	No specific hazards as the ingredients are bound into the uPVC matrix and are thus rendered virtually insoluble.
Softening Point	(Extrusions) 82°C BS 2782 Method 120B.

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale

