

## SAMBROOK INDUCTION MOTORS 240V 50Hz IP44



**APPLICATIONS:** Air compressors, medical instruments and small machine tools, etc.

**FEATURES:** Outstanding performance of starting and operation low noise, compact dimensions and smooth running.

**RATED VOLTAGE:** 220V

YL SERIES - MEDIUM SPEED – 4P (1500RPM)									
Stock Code	Type	KW	HP	Current A	r/min	EFF%	Power Factors	Locked rotor torque	Locked rotor current Rated Current
EKSMOTORZ41010A=	YL80-4	0.75	1	5.1	1400	71	0.92	1.8	29
EKSMOTORZ41015A=	YL90S-4	1.1	1.5	7.3	1400	73	0.95	1.7	40
EKSMOTORZ41020A=	YL90L-4	1.5	2	9.7	1400	75	0.95	1.7	55
EKSMOTORZ41030A=	YL100L-4	2.2	3	13.9	1400	76	0.95	1.7	80
EKSMOTORZ41055A=	YL132S-4	4.0	5.5	27.1	1400	78	0.77	2.2	175
EKSMOTORZ41075A=	YL132L-4	5.5	7.5	31.2	1400	78	0.79	2.2	200
EKSMOTORZ41100A=	YL160S-4	7.5	10	42.5	1400	78	0.79	2.2	259

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale

