

## JUNCTION BOX ONE WAY



|                           |  |
|---------------------------|--|
| <b>DESCRIPTION</b>        | uPVC electrical pathway casing.<br>One-way terminal box terminates a conduit length allowing back to back installations. |
| <b>FEATURES</b>           | - 25mm thread channels.<br>- Constructed with the environment in mind using recycled material                            |
| <b>APPLICATION</b>        | - New electrical installations<br>- Updating old electrical installations  |
| <b>COLOUR</b>             | Black or White   |
| <b>STANDARD</b>           | BS 4607 and BS EN 50085 parts 1 and 2  |
| <b>MATERIAL</b>           | PVCu   |
| <b>LID FIXING CENTRES</b> | 50.8mm   |
| <b>PILLAR THREAD SIZE</b> | M4 (Brass inserts)   |
| <b>ALL CIRCULAR BOXES</b> | Some circular boxes are available with extended lugs for the support of heavy loads.                                     |
| <b>LOAD SUSPENSION</b>    | Standard Circular Box: 3kg. @ 60°C max.  |

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale

