

Product Code		Issue Number	Issue	Issue Date		Issue Reference	
		1		04/07/21		MET008	
Product Description							
uPVC MINI TRUNKING							
Features							
Full range of accessories to compliment including angles, couplers, tees, moulded & painted colour finishes and more.							
Moulded or fabricated a							
Firm locking action defies accidental removal.							
Compliance	BS 476 Part 7, BS 4678 Part 4						
Material uPVC – Flame Retardant							
Finish	White (Standard)		Environmental Information Hazards Identification		C	Packaging Waste: Outer Bag – 0.0034Kg /LDPE RoHS Compliant ref: 2011/65/EU uPVC Products are insoluble in water and will not degrade when buried in landfills etc. The products manufactured and otherwise supplied by thecompany do not have any perceived or known hazardous materials or by-products that would be deemed hazardous to the environment.	
Supplied Length	2.9 Metres				u		
Size	200 x 50 mm				Ti b' h		
		עז <b>1</b>			a	Io specific hazards as the ingredients re bound into the uPVC matrix and are hus rendered virtually insoluble.	
		Softening Point			Extrusions) 82°C BS 2782 Method 120B.		
∠00mm			Any trunking with a space factor equal to or larger than that of the cable factors will satisfactorily accommodate the desired cables				
200	20011111		Thermal			Aetsec uPVC trunking systems are designed to accommodate local thermal expansion and contraction. The coefficient of linear expansion: 7.0 x 10 -5°C to 60°C.	

