



Main

Product or component type	Dimmer
Device presentation	Complete product
Provided equipment	Screws
Dimmer application	Capacitive load Inductive load Ohmic load
Dimmer control	Rotary push type
Load type	Incandescent lamps - 50...250 W - 220...240 V AC High voltage halogen lamp - 50...250 W - 220...240 V AC Electronic transformer - 50...250 VA Dimmable LED - 3...100 W
Colour tint	White
Type of packing	Carton
Quantity per set	Set of 8
Market segment	Small commercial Residential

Complementary

[Ue] rated operational voltage	220...240 V AC 50/60 Hz
Protection type	Thermal fuse Surge arrester
Actuator	Knob
Fixing mode	By screws
Clamping connection capacity	<= 2 x 2.5 mm ² for flexible cable(s) <= 2 x 2.5 mm ² for rigid cable(s)
Wire stripping length	12 mm
Material	Polycarbonate: plastic part Brass: terminals Steel coated with zinc chromate: terminal screw
Device mounting	Flush

Height	86 mm
Width	86 mm
Embedding depth	35 mm

Environment

IP degree of protection	IP20
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	10...95 %
Environmental characteristic	Oil and vapour resistant
Standards	IEC 60669-2-1 CE

Packing Units

Package 1 Weight	116.400 g
Package 1 Height	46.300 mm
Package 1 width	88.000 mm
Package 1 Length	88.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile