



Main

Range	AvatarOn
Device application	Control
Product or component type	Switch
Number of gangs	2 gangs
Colour tint	White

Complementary

Device presentation	Complete product
Device mounting	Flush
Switch function	Curtain
Clamping connection capacity	2 x 2.5 mm ² for solid cable(s) 2 x 2.5 mm ² for stranded cable(s) 3 x 1.5 mm ² for solid cable(s) 3 x 1.5 mm ² for stranded cable(s)
Rated current	10 A at 250 V AC 50/60 Hz
Material	Polycarbonate: grid plate Polycarbonate: base Polycarbonate: dolly Polycarbonate: frame
Load type	Inductive Resistive Fluorescent lamp Incandescent lamp
Connections - terminals	Brass terminal
Embedding depth	22.3 mm
Width	86 mm
Height	86 mm
Depth	32 mm

Environment

Maximum ambient air temperature for operation	35 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000
Standards	GB 16915.1
IP degree of protection	IP20

Packing Units

Package 1 Weight	70.000 g
Package 1 Height	34.000 mm
Package 1 width	86.000 mm
Package 1 Length	86.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile