



### Main

Range	AvatarOn
Product or component type	Shaver socket
Installation direction	Vertical
Input voltage	240 V AC 50/60 Hz
Output voltage	115 V AC 50/60 Hz 240 V AC 50/60 Hz
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: bracket Brass: terminals
Colour tint	White

### Complementary

Device presentation	Complete product
Device mounting	Flush Surface
Cable cross section	1...2.5 mm <sup>2</sup>
Rated operational power in VA	20 VA
Connections - terminals	Pillar terminals
Width	86 mm
Height	147 mm
Depth	50 mm

### Environment

Ambient air temperature for operation	-5...45 °C
Ambient air temperature for storage	0...60 °C
Relative humidity	0...95 %
Environmental characteristic	UV resistant
Operating altitude	2000 m

IP degree of protection	IP21
Standards	IEC 61558-2-5

### Packing Units

Package 1 Weight	150.000 g
Package 1 Height	63.000 mm
Package 1 width	94.000 mm
Package 1 Length	153.000 mm

### Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>