



Main

| | |
|---------------------------|--------------------------------------|
| Range | TeSys |
| Product name | TeSys GC |
| Product or component type | Modular contactor |
| Device short name | GC25 |
| Contacteur application | Motor control Heating Lighting |

Complementary

| | |
|---|---|
| Utilisation category | AC-7B AC-7A |
| Poles description | 2P |
| Power pole contact composition | 2 NO |
| [Ue] rated operational voltage | <= 250 V AC |
| [Ie] rated operational current | 25 A AC-7A 8.5 A AC-7B |
| Operating position | 30°/vertical |
| Control circuit type | AC at 50 Hz |
| [Uc] control circuit voltage | 220...240 V AC 50 Hz |
| [Uimp] rated impulse withstand voltage | 4 kV |
| [Ith] conventional free air thermal current | 25 A (at 50 °C) for power circuit |
| Irms rated making capacity | 68 A at 400 V AC for power circuit conforming to IEC 61095 |
| Rated breaking capacity | 68 A at 400 V for power circuit conforming to IEC 61095 |
| [Icw] rated short-time withstand current | 200 A 40 °C - 10 s for power circuit 62 A 40 °C - 30 s for power circuit |
| Associated fuse rating | 25 A gL at <= 440 V for power circuit |
| Average impedance | 2.5 mOhm - Ith 25 A 50 Hz for power circuit |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

| | |
|---------------------------------|--|
| [Ui] rated insulation voltage | 500 V conforming to IEC 61095 500 V conforming to VDE 0110 |
| Electrical durability | AC-7A: 100000 cycles AC-7B: 100000 cycles |
| Power dissipation per pole | 1.6 W |
| Control type | Remote control |
| Mounting mode | Clip-on |
| Mounting support | DIN rail |
| Standards | IEC 61095 IEC 60947-5 |
| Connections - terminals | Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 1.5 mm ² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² solid without cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 1.5 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 6 mm ² solid without cable end Power circuit: screw clamp terminals 2 cable(s) 4 mm ² solid without cable end |
| Tightening torque | Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 0.8 N.m - on screw clamp terminals |
| Operating time | 10...25 ms opening 10...30 ms closing |
| Mechanical durability | 1000000 cycles |
| Maximum operating rate | 300 cyc/h 50 °C |
| Control circuit voltage limits | Drop-out: 0.2...0.75 U _c at 50 Hz (at <50 °C) Operational: 0.85...1.1 U _c at 50 Hz (at <50 °C) |
| Inrush power in VA | 15 VA 50 Hz (at 20 °C) |
| Hold-in power consumption in VA | 3.8 VA 50 Hz (at 20 °C) |
| Heat dissipation | 1.3 W at 50/60 Hz |

Environment

| | |
|---------------------------------------|--|
| IP degree of protection | IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106 |
| Protective treatment | TC |
| Ambient air temperature for operation | -5...50 °C |
| Ambient air temperature for storage | -40...70 °C |
| Operating altitude | <= 3000 m |
| Mechanical robustness | Shocks contactor open: 10 Gn for 11 ms Shocks contactor closed: 15 Gn for 11 ms Vibrations contactor open: 2 Gn, 5...300 Hz Vibrations contactor closed: 3 Gn, 5...300 Hz |
| Total number of 18 mm modules | 1 |
| Height | 81 mm |
| Width | 17.5 mm |
| Depth | 62.5 mm |
| Net weight | 0.11 kg |
| Quantity per set | Set of 12 |
| Colour | White |

Packing Units

| | |
|------------------------------|-------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 121 g |
| Package 1 Height | 8 cm |

| | |
|------------------------------|-----------|
| Package 1 width | 9.5 cm |
| Package 1 Length | 23 cm |
| Unit Type of Package 2 | BB1 |
| Number of Units in Package 2 | 12 |
| Package 2 Weight | 1.46 kg |
| Package 2 Height | 8 cm |
| Package 2 width | 9.5 cm |
| Package 2 Length | 23 cm |
| Unit Type of Package 3 | S03 |
| Number of Units in Package 3 | 144 |
| Package 3 Weight | 18.197 kg |
| Package 3 Height | 30 cm |
| Package 3 width | 30 cm |
| Package 3 Length | 40 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| RECh Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|