



Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
Total system power	50 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	Ra=80
Luminous flux	5000 lm
Bulb lifespan	50000 h
Colour temperature	6500 K
Colour	Black
Beam angle	110 °
Shape	Rectangular
Height	215.4 mm
Width	161.4 mm
Depth	31.0 mm
Product weight	1.02 kg

Environment

Environmental characteristic	Weatherproof
IP degree of protection	IP65
IK degree of protection	IK05
Ambient air temperature for operation	-30...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.15 kg
Package 1 Height	4.8 cm
Package 1 width	17 cm
Package 1 Length	22.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	10
Package 2 Weight	11.941 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P12
Number of Units in Package 3	160
Package 3 Weight	203.056 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information