# Product data sheet Characteristics

# NSYCRN64200P

Spacial CRN plain door with mount.plate. H600xW400xD200 IP66 IK10 RAL7035...





#### Main

Range	Spacial	
Product name	Spacial CRN	
Device application	Multi-purpose	
Product or component type	Compact enclosure	
Enclosure nominal height	600 Mm	
Enclosure nominal width	400 Mm	
Enclosure nominal depth	200 Mm	
Installation accessory type	Wall-mounting	
Device composition	1 body 1 cable gland plate 1 door with lock 1 mounting plate	
Door type	Plain	
Mounting plate description	Plain	

#### Complementary

Complementary		
Variant particularity	Sides made from a single folded section  Back welded with double profile forming a protected sealed area	
Number of doors	Front face: 1 door(s)	
Door opening side	Reversible (120 °)	
Lock type	3 mm double-bar lock	
Type of gland plate	Standard	
Accessibility for operation	Front	
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Enclosure: steel Mounting plate: galvanised steel	
Surface finish	Enclosure: epoxy-polyester powder	
Colour	Enclosure: grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	CUL UL DNV-GL	
Net weight	12.813 Kg	

#### Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	12.811 Kg	
Package 1 Height	21.5 Cm	
Package 1 width	41.5 Cm	
Package 1 Length	61 Cm	

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty 18 months	_
--------------------	---

Product Life Status : Commercialised