## Product data sheet Characteristics

# NSYTBS342912

ABS box IP66 IK07 RAL7035 Int.H325W275D120 Ext.H341W291D128 Opaque cover H20





#### Main

Range	Thalassa
Product name	Thalassa TBS
Device application	Multi-purpose
Product or component type	Industrial box
Height	341 Mm
Width	291 Mm
Depth	128 Mm
Internal height	325 Mm
Internal width	275 Mm
Internal depth	120 Mm
Enclosure mounting	Wall mounted
Device composition	1 body
	1 cover
	4 cover screw
Body type	One piece moulded
Type of front cover	Low plain cover
Cover fixing	Plastic screws
Lock type	Captive screw flat outside sealed area
Removable parts	Cover by captive screws

#### Complementary

Material	ABS (acrylonitrile butadiene-styrene)	
Colour	Grey (RAL 7035)	
Standards	IEC 62208	
Product certifications	TÜV	
Electrical insulation class	Class II	
IP degree of protection	IP66 conforming to NEMA 4.4X	
IK degree of protection	IK07 conforming to IEC 62262	
Fire resistance	650 °C conforming to IEC 60695-2-11	
Ambient air temperature for storage	-1540 °C	
Ambient air temperature for operation	-2560 °C	
Net weight	1.16 Kg	

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.387 Kg
Package 1 Height	14 Cm
Package 1 width	30 Cm
Package 1 Length	35 Cm
Unit Type of Package 2	BB1
Number of Units in Package 2	4
Package 2 Weight	6.241 Kg
Package 2 Height	40 Cm
Package 2 width	41 Cm
Package 2 Length	60 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <sup>™</sup> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☑ China RoHS Declaration

# Contractual warranty

Warranty	18 months
----------	-----------

Product Life Status : Commercialised