Product data sheet Characteristics

LV429407

MN undervoltage release, ComPact NSX, rated voltage 220/240 VAC 50/60 Hz, 208/277 VAC 60 Hz





Main

Device short name	MX	
Product or component type	Voltage release	
Device application	Control	
Range compatibility	ComPact NSX EasyPact CVS PowerPact Multistandard ComPact NSX DC	
Voltage release type	Undervoltage release	
[Uc] control circuit voltage	208277 V AC 60 Hz 220240 V AC 50/60 Hz	:

Complementary

Componentary		<u>u</u>
Threshold tripping voltage	0.350.7 x Un opening 0.85 x Un closing	
Supply holding power	5 VA	
Supply inrush power	10 VA	
Mounting mode	Fixed	<u>4</u>
Response time	50 ms	
Auxiliary connection terminal	Screw terminal 01.5 mm²	

Packing Units

Package 1 Length	8 cm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	
Package 2 Weight	1.356 kg	
Package 2 Height	15 cm	
Package 2 width	9 cm	
Package 2 Length	23 cm	
Unit Type of Package 3	S03	
Number of Units in Package 3	60	
Package 3 Weight	8.62 kg	
Package 3 Height	30 cm	
Package 3 width	30 cm	
Package 3 Length	40 cm	

Offer Sustainability

Sustainable offer status	e offer status Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

Contractual warranty

Warranty	18 m	onths