



Main

Device short name	MT100/160
Product or component type	Motor mechanism
Device application	Automatic spring charging
Range compatibility	ComPact NSX100 ComPact NSX160 Compact NSX100 DC Compact NSX160 DC PowerPact Multistandard EasyPact CVS100 EasyPact CVS160 PowerPact J PowerPact H
Control type	Standard
[Uc] control circuit voltage	208...277 V AC 60 Hz 220...240 V AC 50/60 Hz
Circuit breaker mounting mode	Fixed
Circuit breaker frame rated current	160 A 100 A

Complementary

Control signal type	Impulse Maintained
Response time	< 700 ms (opening) < 80 ms (closing)
Maximum operating frequency	4 per minute
Maximum power consumption in VA	500 VA closing 500 VA opening
Provided equipment	SDE adaptor
Locking options description	Padlocking in OFF position

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1.39 kg
Package 1 Height	11.7 cm
Package 1 width	10.5 cm
Package 1 Length	17 cm
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Weight	21.774 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Contractual warranty

Warranty	18 months
----------	-----------