## Product data sheet Characteristics

# XUK0ARCTL2T

Photoelectric sensors XU, XUK, emitter, 24...240 VAC, cable 2 m





### Main

Telemecanique Photoelectric sensors XU	
General purpose multimode	
Photo-electric sensor transmitter	
XUK	
Compact 50 x 50	
Thru beam	
Plastic	
AC/DC	
2-wire	
Cable	
2 M	
-	
Infrared thru beam	
30 M thru beam need a receiver	
	General purpose multimode Photo-electric sensor transmitter XUK Compact 50 x 50 Thru beam Plastic AC/DC 2-wire Cable 2 M - Infrared thru beam

#### Complementary

Complementary	
Enclosure material	PBT
Lens material	PMMA
Maximum sensing distance	35 M thru beam
Add on input	Test by emission breaking
Wire insulation material	PvR
Status LED	1 LED (green) for supply on
[Us] rated supply voltage	12240 V DC 24240 V AC
Supply voltage limits	10264 V DC 20264 V AC
Switching capacity in mA	3 A (cos $\phi$ = 1 for 0.5 million cycles at 1 operating cycle per second at 250 V)
Switching frequency	<= 20 Hz
Maximum voltage drop	<1.5 V (closed state)
Time delay range	010 s monostable, on-delay or off-delay (programmable) delay
Setting-up	Without sensitivity adjustment
Depth	50 Mm
Height	50 Mm
Width	18 Mm

### Environment

Product certifications	CSA
Product Certifications	
	CE
	UL
Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4070 °C
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP65 double insulation conforming to IEC 60529

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	154 G
Package 1 Height	13.2 Cm
Package 1 width	9.5 Cm
Package 1 Length	4.2 Cm
Unit Type of Package 2	S02
Number of Units in Package 2	22
Package 2 Weight	3.752 Kg
Package 2 Height	15 Cm
Package 2 width	30 Cm
Package 2 Length	40 Cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California tocause birth defects or other reproductive harm. For more information goto www.P65Warnings.ca.gov

### Contractual warranty

Warranty 18 months	Warranty
--------------------	----------

Product Life Status : Commercialised

