# Product data sheet Characteristics

# ZCKY59

Limit switch lever, Limit switches XC Standard, ZCKY, thermoplastic plastic round rod 6 mm L=200 mm, -40...70 °C



#### Main

I		
■ Main		
Range of product	Telemecanique Limit switches XC Standard	
Series name	Standard format	
Product or component type	Limit switch lever	
Device short name	ZCKY	
Product compatibility	XCKL XCKJ XCKM XCKS	
Associated head	ZCKD05 ZCKE05	
Movement of operating head	Rotary	
Type of operator	Rod lever spring return thermoplastic (round rod 6 mm, L = 200 mm)	
Type of approach	Lateral approach	
Complementary		
Switch actuation	By any moving part	
Positive opening	Without	
Environment		
Ambient air temperature for operation	-2570 °C for standard environment -4070 °C for low temperature	
Ambient air temperature for storage	-4070 °C standard environment -4070 °C low temperature	
Environmental characteristic	Standard environment Low temperature	
lup 18, 2021		

#### Complementary

Switch actuation	By any moving part
Positive opening	Without

#### Environment

Ambient air temperature for operation	-2570 °C for standard environment -4070 °C for low temperature
Ambient air temperature for storage	-4070 °C standard environment -4070 °C low temperature
Environmental characteristic	Standard environment Low temperature



### Packing Units

Package 1 Weight	0.025 kg	
Package 1 Height	0.100 dm	
Package 1 width	0.250 dm	
Package 1 Length	2.020 dm	

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

## Contractual warranty

Warranty

18 months