Product data sheet Characteristics

MTN3105-0000

Two-circuit swit.insrt 1P w. indic.light,flushmntd,10 AX, AC 250 V, screwl.





Main

Man		5
Range of product	Merten inserts	
Product or component type	Switch	ž
Device presentation	Mechanism	3

Complementary

Switch function	1-pole 1-way	
Actuator	Rocker	
Device mounting	Flush	
Fixing mode	By screws and claws	
[Ue] rated operational voltage	250 V	
Rated current	10 AX	
Maximum switching current	10 A	7
Number of rocker	2	-
Pilot light	Red indicator	***
Connections - terminals	Screwless terminals	<u>.</u> .
Material	Metal Plastic	
		· · · · · · · · · · · · · · · · · · ·

Environment

IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	68 g	
Package 1 Height	3.7 cm	

Package 1 width	7.1 cm
Package 1 Length	7.1 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	802 g
Package 2 Height	18 cm
Package 2 width	9 cm
Package 2 Length	27 cm
Unit Type of Package 3	S03
Number of Units in Package 3	40
Package 3 Weight	3.7 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months	
----------	-----------	--