



Main

| | |
|---------------------------|-------------------|
| Range | TeSys |
| Device short name | LUA1 |
| Product or component type | Auxiliary contact |

Complementary

| | |
|---|--|
| Auxiliary contact composition | 1 NO + 1 NC |
| Signalling function | Fault signalling Indicating rotary knob in ready position |
| [Ue] rated operational voltage | <= 250 V AC <= 250 V DC |
| [Ui] rated insulation voltage | 250 V conforming to CSA 250 V conforming to IEC 60947-5-1 250 V conforming to UL |
| [Ith] conventional free air thermal current | 2.5 A |
| Minimum switching voltage | 17 V |
| Minimum switching current | 5 mA |
| Net weight | 0.03 kg |
| Connections - terminals | Screw clamp terminals |

Packing Units

| | |
|------------------|----------|
| Package 1 Weight | 25.000 g |
| Package 1 Height | 0.200 dm |
| Package 1 width | 0.900 dm |
| Package 1 Length | 1.200 dm |

Offer Sustainability

| | |
|--------------------------|-----------------------|
| Sustainable offer status | Green Premium product |
|--------------------------|-----------------------|

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|