# Product datasheet Characteristics

## **GU6412CSS**

Ultimate Screwless dimmer switch 400W/VA, 1gang, 2way, main & LV, st.steel



-1	١/	2	п	n

TTT COLOR		2.
Range of product	Ultimate	
Range	Ultimate	2
Aesthetic name	Screwless flat plate	
Product or component type	Dimmer	
Device application	Control	
Load type	Incandescent lamp 230 V AC halogen lamp: 400 W	in pour
Colour tint	Stainless steel	y 4 €
Quantity per set	Set of 1	C A <u>H</u>

#### Complementary

		<u> </u>
Switch function	2-way	ila Ila
Device mounting	Wall mounted	, i
Dimmer application	Resistive load Inductive load	deremin
[Ue] rated operational voltage	230 V AC 50 Hz	
Number of gangs	1 gang	
Connections - terminals	Screwless terminals	
Fixing mode	By screws M3.5 x 25 mm	<u>.v</u>
Height	88 mm	-
Width	88 mm	् <u>व</u>
Depth	25 mm	het in

#### Environment

Standards	BS EN 60669-2-1	- 5
IP degree of protection	IP20	_ c

#### **Packing Units**

Package 1 Weight	209.000 g	- 0
Package 1 Height	94.000 mm	Ė

Package 1 width	55.000 mm
Package 1 Length	96.000 mm

### Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins