



## Commercial status

Discontinued on: 23 January 2021

End-of-service on: 24 January 2021

KB25\_WE has not been replaced. Please contact your customer care centre for more information.

⚠ Restricted Sales for Services

## Main

Range	Vivace
Product or component type	Socket-outlet with switch
Device short name	KB25
Device application	Power supply Control
Device presentation	Complete mechanism

## Complementary

Outlet poles configuration	2P + E
Number of gangs	2 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	35 mm
Rated current	13 A at 250 V AC, resistive
Network frequency	50 Hz
Contacts material	Brass and phosphor bronze
Connections - terminals	Pillar terminal
Terminal identifier	Earth L N
Tightening torque	0.4 N.m

Clamping connection capacity	3 x 2.5 mm <sup>2</sup> 2 x 4 mm <sup>2</sup>
Width	147 mm
Height	87 mm

## Environment

Standards	MS 589 BS 1362-2 SS 145
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

## Packing Units

Package 1 Weight	148.000 g
Package 1 Height	31.000 mm
Package 1 width	86.000 mm
Package 1 Length	146.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>