Product datasheet Characteristics

KB31TV_WE 1 GANG TV CO-AXIAL OUTLET



| -1 | ١, | n | т | n |
|----|----|---|---|---|
| | | | | |

| Range | Vivace | |
|---------------------------|----------------------|--|
| Device short name | KB31 | |
| Product or component type | TV socket | |
| Device application | Media device support | |
| Device presentation | Complete mechanism | |

Complementary

| Range | Vivace | |
|---------------------------------------|---|--|
| Device short name | KB31 | |
| Product or component type | TV socket | |
| Device application | Media device support | |
| Device presentation | Complete mechanism | |
| Complementary | | |
| Number of gangs | 1 gang | |
| Number of outputs | 1 | |
| Colour tint | White | |
| Material | Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: base | |
| Projecting depth | 8 mm | |
| Device mounting | Flush | |
| Mounting support | Wall mounted | |
| Fixing mode | By screw M3.5 | |
| Fixing center | 60.3 mm | |
| Embedding depth | 35 mm | |
| Connections - terminals | Clamp terminal | |
| Tightening torque | 0.4 N.m | |
| Width | 87 mm | |
| Height | 87 mm | |
| Environment | | |
| Ambient air temperature for operation | -540 °C | |
| | 095 % | |
| Relative humidity | | |

Environment

| Ambient air temperature for operation | -540 °C |
|---------------------------------------|------------|
| Relative humidity | 095 % |
| Environmental characteristic | Indoor use |

Packing Units

| Package 1 Weight | 58.400 g | |
|------------------|-----------|--|
| Package 1 Height | 86.000 mm | |
| Package 1 width | 50.000 mm | |
| Package 1 Length | 86.000 mm | |

Offer Sustainability

| EU RoHS Directive | Compliant EU RoHS Declaration |
|----------------------------|--|
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| Environmental Disclosure | Product Environmental Profile |