Product datasheet Characteristics

KB32_WE Vivace 16AX 250V 2gang 2Way Switch, White





Commercial status

Discontinued on: 23 January 2021

End-of-service on: 24 January 2021

KB32_WE has not been replaced. Please contact your customer

care centre for more information.

Main

Range	Vivace	4
Product or component type	Switch	
Device short name	KB32	
Device application	Control	
Device presentation	Complete mechanism	

Complementary

Main		
Range	Vivace	
Product or component type	Switch	
Device short name	KB32	
Device application	Control	
Device presentation	Complete mechanism	
Complementary		
Switch function	2-way	
Actuator	Rocker	
Number of gangs	2 gangs	
Colour tint	White	
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base	
Projecting depth	8 mm	
Device mounting	Flush	
Mounting support	Wall mounted	
Fixing mode	By screw M3.5	
Fixing center	60.3 mm	
Embedding depth	35 mm	
Rated current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent	
[Ue] rated operational voltage	250 V AC	
Network frequency	50 Hz	
Contacts material	Brass and phosphor bronze	
Connections - terminals	pillar terminal	
Terminal identifier	L2 COM L1	

Tightening torque	0.4 N.m
Clamping connection capacity	2.5 mm²
Width	87 mm
Height	87 mm

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1
Ambient air temperature for operation	-540 °C
Relative humidity	095 %
Environmental characteristic	Indoor use

Packing Units

Package 1 Weight	72.000 g	
Package 1 Height	4.000 cm	
Package 1 width	8.500 cm	
Package 1 Length	8.500 cm	

Offer Sustainability

Offer Sustamability		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	onmental Disclosure Product Environmental Profile	