



### Main

Range of product	Vivace
Range	Vivace
Device short name	KB32
Product or component type	TV/FM socket
Device presentation	Complete mechanism

### Complementary

Number of gangs	1 gang
Number of outputs	2
Colour tint	White
Material	Polycarbonate: surround Polycarbonate: grid plate Polycarbonate: base
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	60.3 mm
Embedding depth	35 mm
Tightening torque	0.4 N.m
Width	86 mm
Height	86 mm

### Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	Indoor use

## Packing Units

Package 1 Weight	72.800 g
Package 1 Height	86.000 mm
Package 1 width	22.000 mm
Package 1 Length	86.000 mm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------