



### Main

Range	Vivace
Product or component type	USB charger
Fixing mode	Screw

### Complementary

Device mounting	Flush
Device presentation	Mechanism
Colour tint	White
Surface finish	Glossy
Surface treatment	Untreated
Number of modules	2 modules 46 x 36.7 x 21.7 mm
Condition of use	Room temperature
Ambient air temperature for storage	-5...60 °C
Relative humidity	10...90 %
[Ue] rated operational voltage	100/240 V AC 50/60 Hz
Integrated connection type	2 USB port 5 V DC, maximum load current: 2.1 A
Material	PA (polyamide) 6: housing Silicone rubber: cover PC (polycarbonate): grid plate
Shape of screw head	Cross
Number of terminals	2 screw terminals
Clamping connection capacity	2.5 mm <sup>2</sup> for stranded cable(s) 2.5 mm <sup>2</sup> for flexible cable(s) 2.5 mm <sup>2</sup> for rigid cable(s) 1.5 mm <sup>2</sup> for stranded cable(s) 1.5 mm <sup>2</sup> for flexible cable(s) 1.5 mm <sup>2</sup> for rigid cable(s)
Wire stripping length	6 mm
Product compatibility	Major smart phone and tablet HTC Samsung HW Apple XiaoMi

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

	Power bank
Height	87 mm
Width	87 mm
Depth	39 mm
Embedding depth	29.3 mm
Net weight	0.1042 kg

## Environment

Product certifications	CCC IEC
IP degree of protection	IP20
Environmental characteristic	Liquid soap Alcohol

## Packing Units

Package 1 Weight	102.000 g
Package 1 Height	86.000 mm
Package 1 width	35.000 mm
Package 1 Length	86.000 mm

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)