



Main

Range of product	Vivace
Device short name	KB33
Product or component type	TV/FM/SAT socket
Device presentation	Complete mechanism

Complementary

Colour tint	White
Material	Polycarbonate: surround Polycarbonate: grid plate
Maximum insertion loss	2 dB (+/- 1.5 dB) at 88...125 MHz (IN-FM) 1 dB (+/- 1.5 dB) at 40...70 MHz (IN-TV) 2 dB (+/- 1.5 dB) at 174...862 MHz (IN-TV) 2 dB (+/- 1.5 dB) at 950...2150 MHz (IN-SAT) 2 dB (+/- 1.5 dB) at 2150...2400 MHz (IN-SAT)
Minimum return loss	5 dB 40...2400 MHz IN 8 dB 87.5...125 MHz FM-SAT 5 dB 40...862 MHz TV 5 dB
Isolation	20 dB at 88...108 MHz (TV-FM) 6 dB at 40...2400 MHz (TV-SAT) 30 dB at 40...860 MHz (FM-SAT)
TV connector	Male IEC
Radio connector	Male IEC
SAT connector	Female F type
Average impedance	75 Ohm
Projecting depth	36.2 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Fixing center	60.3 mm
Embedding depth	35 mm
Connections - terminals	Cable terminal
Tightening torque	0.4 N.m
Width	86 mm
Height	86 mm
Net weight	110 g

Environment

Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Environmental characteristic	No exposure to direct radiation from sunlight

Packing Units

Package 1 Weight	142.000 g
Package 1 Height	24.000 mm
Package 1 width	86.000 mm
Package 1 Length	86.000 mm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------