



### Main

Range	Vivace
Product or component type	Switch
Device short name	KB34
Device application	Lighting
Device presentation	Complete product
Additional switch application	Switch

### Complementary

Switch function	1-way
Actuator	Rocker
Number of gangs	4 gangs
Colour tint	White
Material	Polycarbonate: grid plate Polycarbonate: surround Nylon: base
Surface finish	Glossy
Surface treatment	Untreated
Type of packing	Plastic bag
Quantity per set	1
Projecting depth	8 mm
Device mounting	Flush
Mounting support	Wall mounted
Fixing mode	By screw M3.5
Fixing center	120.6 mm
Embedding depth	35 mm
Rated current	16 AX at 250 V AC, inductive 16 AX at 250 V AC, fluorescent
[Ue] rated operational voltage	250 V AC

Network frequency	50/60 Hz
Connections - terminals	8 pillar terminal
Terminal identifier	COM L1
Tightening torque	0.4 N.m
Clamping connection capacity	<= 2.5 mm² for rigid or stranded cable(s)
Wire stripping length	12 mm
Width	146 mm
Height	86 mm
Depth	36 mm

## Environment

Standards	IEC 60669-1 SS 227 MS IEC 60669-1
Ambient air temperature for operation	-5...40 °C
Relative humidity	0...95 %
Operating altitude	0...2000 m
Environmental characteristic	Indoor use
IP degree of protection	IP20

## Packing Units

Package 1 Weight	136.000 g
------------------	-----------

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>