



## Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Switched socket
Device presentation	Complete product
Outlet standard	British
Colour tint	Matt white
Quantity per set	Set of 10
Type of packing	Carton

## Complementary

Switch function	1-pole
Rated current	13 A at 230 V AC 50 Hz
Actuator	Rocker
Number of gangs	1 gang
Pilot light	without LED
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	33 mm
Width	87 mm
Height	87 mm
Net weight	0.092 kg

## Environment

Standards	BS 1363-2
-----------	-----------

IP degree of protection	IP20
-------------------------	------

## Packing Units

Package 1 Weight	92.000 g
------------------	----------

## Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>