



## Main

Range	Lisse
Aesthetic name	White moulded
Product or component type	Switched socket
Device presentation	Complete product
Outlet standard	British
Colour tint	Matt white
Quantity per set	Set of 5
Type of packing	Carton

## Complementary

Switch function	1-pole
Rated current	13 A at 250 V AC 50 Hz
Actuator	Rocker
Number of gangs	2 gangs
Pilot light	without LED
Fixing mode	By screws
Connections - terminals	Screw terminals
Material	Urea (carbamide)
Type of installation	Indoor
Depth	36 mm
Width	149 mm
Height	87 mm
Net weight	0.149 kg

## Environment

Standards	BS 1363-2
-----------	-----------

IP degree of protection	IP20
-------------------------	------

## Packing Units

Package 1 Weight	150.000 g
------------------	-----------

## Offer Sustainability

Sustainable offer status	Green Premium product
RECh Regulation	<a href="#">RECh Declaration</a>
RECh free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End of Life Information</a>