## Product data sheet Characteristics

# RUZC2M

Harmony, Socket, for RUMC2 relays, 10 A, screw connectors, mixed contact





#### Main

Range of product	Harmony Electromechanical Relays Harmony Timer Relays
Product or component type	Socket
Contact terminal arrangement	Mixed
Product compatibility	Plug-in relay RUM with 2 C/O contact Plug-in relay RE48 with 2 C/O contact Plug-in relay RE48 with 1 C/O + 1 C/O contact
Shape of pin	Cylindrical
Device short name	RUZ
Sale per indivisible quantity	10

#### Complementary

17 7 1 1 1		
Main		
Range of product	Harmony Electromechanical Relays Harmony Timer Relays	
Product or component type	Socket	
Contact terminal arrangement	Mixed	
Product compatibility	Plug-in relay RUM with 2 C/O contact Plug-in relay RE48 with 2 C/O contact Plug-in relay RE48 with 1 C/O + 1 C/O contact	
Shape of pin	Cylindrical	
Device short name	RUZ	
Sale per indivisible quantity	10	
Complementary		
[Ith] conventional free air thermal current	10 A	
[Ue] rated operational voltage	< 250 V	
Tightening torque	< 1 N.m for M3.5 screw(s)	
Fixing mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)	
Marking	CE	
Width	38 mm	
Net weight	0.054 kg	
Environment		
Connections - terminals	Connector, 1 x 0.251 x 2.5 mm <sup>2</sup> (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm <sup>2</sup> (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm <sup>2</sup> (AWG 20AWG 14) solid without cable end	
	Connector, 2 x 0.52 x 1.5 mm <sup>2</sup> (AWG 20AWG 16) solid without cable end	

#### Environment

Connections - terminals	Connector, 1 x 0.251 x 2.5 mm <sup>2</sup> (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm <sup>2</sup> (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm <sup>2</sup> (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm <sup>2</sup> (AWG 20AWG 16) solid without cable end
Standards	IEC 61984



Product certifications	UL CSA
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-4055 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

### Packing Units

PCE
1
55 g
8 cm
8 cm
13.7 cm
BB1
10
600 g
8.4 cm
8.4 cm
14.4 cm
S03
200
11.327 kg
30 cm
30 cm
40 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

## Contractual warranty

Warranty

18 months

Product data sheet Dimensions Drawings

#### Socket





