## Product data sheet Characteristics

# **RUZSC2M**

Harmony, Socket, for RUMC2 relays, 12 A, screw connectors, separate contact





#### Main

Widin	
Range of product	Harmony Electromechanical Relays
Product or component type	Socket
Contact terminal arrangement	Separate
Product compatibility	Plug-in relay RUM with 2 C/O contact
Shape of pin	Cylindrical
Device short name	RUZ
Sale per indivisible quantity	10

#### Complementary

Main		
Range of product	Harmony Electromechanical Relays	
Product or component type	Socket	
Contact terminal arrangement	Separate	
Product compatibility	Plug-in relay RUM with 2 C/O contact	
Shape of pin	Cylindrical	
Device short name	RUZ	
Sale per indivisible quantity	10	
Complementary		
[Ith] conventional free air thermal	12 A	
current		
[Ue] rated operational voltage	< 250 V	
Tightening torque	< 1 N.m for M3.5 screw(s)	
Fixing mode	By screw (panel) Clip-on (35 mm symmetrical DIN rail)	
Marking	CE	
Width	36 mm	
Net weight	0.095 kg	
Environment		
Connections - terminals	Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end	
Standards	IEC 61984	
	UL	
Product certifications	CSA	

#### Environment

Connections - terminals	Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end	office some services and services are services and services are services are services and services are services are services are services and services are servic
Standards	IEC 61984	
Product certifications	UL CSA	This doc
Ambient air temperature for storage	-4085 °C	

Ambient air temperature for operation	-4055 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	73 g
Package 1 Height	10.5 cm
Package 1 width	9 cm
Package 1 Length	18 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	733 g
Package 2 Height	9 cm
Package 2 width	10.5 cm
Package 2 Length	18 cm
Unit Type of Package 3	S03
Number of Units in Package 3	160
Package 3 Weight	12.222 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov


#### Contractual warranty

Warranty	18 months

# Product data sheet Dimensions Drawings

# **RUZSC2M**

#### **Dimensions**




- (1) Relays
- (2) Protection module
- (3) Maintaining clamp
- (4) 2 bus jumpers

# Product data sheet Connections and Schema

# **RUZSC2M**

## Wiring Diagram




Symbols shown in blue correspond to Nema marking.

## Product data sheet Connections and Schema

## **RUZSC2M**

### Bus Jumpers Mounting on Sockets with Separate Contacts

Example of RUZS2 bus jumper mounting on sockets (view from below)



- (1) 2 bus jumpers (polarity A2)
- (2) 2 bus jumpers (polarity A1)