Product datasheet Characteristics

RXZE2M114M

Harmony, Socket, for RXM2/RXM4 relays, screw connectors, mixed contact





Main

Man		2
Range of product	Harmony Electromechanical Relays Harmony Timer Relays	
Product or component type	Socket	
Contact terminal arrangement	Mixed	
Product compatibility	Plug-in relay RXM with 2 C/O contact Plug-in relay RXM with 4 C/O contact	y villido
Shape of pin	Flat	
Device short name	RXZ)
Sale per indivisible quantity	10	

Complementary

10 A	<u>.</u>
< 250 V	
Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end	. c. po
< 1 N.m for M3 screw(s)	
By screw (panel) Clip-on (35 mm symmetrical DIN rail)	000
CE	
27 mm	
0.056 kg	
	< 250 V Connector, 1 x 0.251 x 2.5 mm² (AWG 22AWG 14) flexible with cable end Connector, 2 x 0.252 x 1 mm² (AWG 22AWG 17) flexible with cable end Connector, 1 x 0.51 x 2.5 mm² (AWG 20AWG 14) solid without cable end Connector, 2 x 0.52 x 1.5 mm² (AWG 20AWG 16) solid without cable end < 1 N.m for M3 screw(s) By screw (panel) Clip-on (35 mm symmetrical DIN rail) CE 27 mm

Environment

Standards	IEC 61984
Product certifications	UL

	CSA Lloyd's
Ambient air temperature for storage	-4085 °C
Ambient air temperature for operation	-4055 °C
IP degree of protection	IP20 conforming to EN/IEC 60529
Dielectric strength	2500 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	54 g
Package 1 Height	4.3 cm
Package 1 width	2.7 cm
Package 1 Length	8 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	574 kg
Package 2 Height	7.7 cm
Package 2 width	9.2 cm
Package 2 Length	14.2 cm
Unit Type of Package 3	S02
Number of Units in Package 3	120
Package 3 Weight	30.52 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins


Contractual warranty

Warranty	18 months
----------	-----------

RXZE2M114M

Socket

Socket with Mixed Contact Terminals and Connector



- 1 Relay
- 2 Protection Module
- 3 Carriage Stirrup