



SINOVA, Miniature Circuit Breaker 415V 6kA, 4-pole C, 10 A

General technical data	
number of poles	4
design of pole	4P
tripping characteristic class	C
overvoltage category	III
degree of pollution	2
Supply voltage	
supply voltage at AC rated value	415 V
protection class IP	IP20, with connected conductors
switching capacity current	6 kA
• according to EN 60898 rated value	
power loss [W]	1.8 W
• for rated value of the current at AC in hot operating state per pole	
• maximum	
product feature silicon-free	Yes
product extension installable supplementary devices	No
connectable conductor cross-section solid	1 mm ²
• minimum	
• maximum	
connectable conductor cross-section stranded	1 mm ²
• minimum	
• maximum	
tightening torque with screw-type terminals	2 N·m
• minimum	
• maximum	
position of power supply cord	Any
height	84 mm
width	72 mm
depth	76 mm
installation depth	70 mm
number of modular width units	4
fastening method	DIN rail
mounting position	any
net weight	360 g
ambient temperature during operation	-25 °C
• minimum	
• maximum	
ambient temperature during storage	-40 °C
• minimum	

- maximum

75 °C

reference code

- according to EN 61346-2
- according to IEC 81346-2

F
F

Further information

Siemens has decided to exit the Russian market (see here).

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mifb=5TJ6410-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TJ6410-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mifb=5TJ6410-7


CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>





last modified:

11/21/2022 

