










LED Slim Down Light - Recessed Round (RR)

The Slim Downlight Start range of recessed luminaires designed to replace traditional CFL downlighters directly and affordably. The products' slim design fits in narrow spaces but can be used in any location where 6 inch or 8 inch downlighters are needed.



Benefits

- Functional design
- One-to-one replacement for conventional luminaires
- Up to 60% energy saving compared to CFL solutions
- Affordable solution for retrofit or new installations
- Reduced replacement and maintenance costs
- Shalow installation depth
- Wire spring leaf for secure installation













- . Die-cast Aluminum heat sink
- . Drivers independently y designed for the product's reliability and durability.
- . Ultra-Thin suitable for all intergrated ceiling application on
- . Energy saving to 55% VS. traditional downlight and longer life
- . Multiple type choice for Round, Round surface, square and square
- . Multiple col or temperature available: 2700K to 6500K
















Slim Downlight Recessed Round (RR)















Product Description	Product Code	Wattage (W)	Lumen (lm)	CCT (K)	System Efficiency (lm/W)	Dimensions (mm)	Weight (kg)	Pack Qty
Slim Downlight Recessed Round (RR)								
SAMBROOK LED CEILING LIGHT RECESSED 2" ROUND 5000K/6500K	ESUPLFLEDCEA03A	3	1 140	3000	76	Ø170×11	0.25	1
SAMBROOK LED CEILING LIGHT RECESSED 2" ROUND 3000K	ESUPLFLEDCEA03B	3	1 250	4000	83	Ø170×11	0.25	1
SAMBROOK LED CEILING LIGHT RECESSED 4" ROUND 5700K/6500K	ESUPLFLEDCEA09A	9	1 550	3000	86	Ø225x11	0.34	1
SAMBROOK LED CEILING LIGHT RECESSED 4" ROUND 3000K/4000K	ESUPLFLEDCEA09B	9	1 680	4000	93	Ø225x11	0.34	1
SAMBROOK LED SLIM CEILING LIGHT RECESSED ROUND 3000K	ESAMLFCERR3012A	12	1 900	3000	86	Ø225x11	0.34	1
SAMBROOK LED SLIM CEILING LIGHT RECESSED ROUND 6500K	ESAMLFCERR6512A	12	2 050	4000	93	Ø225x11	0.34	1





