



# Ultraslim LED Panel

## Surface / Recessed

### PRODUCT SPECIFICATIONS:

#### Features:

- Energy efficient and low heat dissipation
- Flicker free driver
- Easy to install
- No UV & IR
- PMMA LGP
- Environment friendly
- Instant light with low running temperatures
- Average lifetime: 30000hrs
- Operating temp: -10°C to 45°C

#### Housing:

Round aluminium powder coated white with pressure die cast housing

#### Optics:

High transmittance polystyrene opal diffuser for glare-free symmetric light distribution

These slim fit low profile downlights re engineered to deliver superior light output and uniformity. They are an ideal solution where ceiling voids are limited but high lumen output is required.

TECHNICAL SPECIFICATIONS						
Product Desc.	Watts	Input Voltage	Driver	Lumen Output	CCT	Dimensions
Round Recessed	3W	85-265V	Isolated	160lm	3000K/4000K/6000K	Dia.: 88mm
Round Recessed	6W	85-265V	Isolated	420lm	3000K/4000K/6000K	Dia.:120mm
Round Recessed	9W	85-265V	Isolated	630lm	3000K/4000K/6000K	Dia.:145mm
Round Recessed	12W	85-265V	Isolated	1080lm	3000K/4000K/6000K	Dia.:170mm
Round Recessed	15W	85-265V	Isolated	1350lm	3000K/4000K/6000K	Dia.:190mm
Round Recessed	18W	85-265V	Isolated	1800lm	3000K/4000K/6000K	Dia.:225mm
Round Surface	12W	85-265V	Isolated	1080lm	3000K/4000K/6000K	Dia.:170 - 32mm
Round Surface	18W	85-265V	Isolated	1800lm	3000K/4000K/6000K	Dia.:225 - 32mm

Other Options: Emergency & dimmable versions available on request

# APPLICATIONS

- Residences
- Restaurants
- Hotel lobbies / Waiting areas
- Modern gyms / Spa
- Corporate offices

