



Applications:


- Residences
- Restaurants


•

- Hotel Rooms / Bathrooms
- Modern Gyms / Spa
- Corporate Offices

LED lamp with low power consumption, long life, good stability, and high reliability.

CCT 3000K 4000K 6000K





Note: The curve is the illumination area and the average illuminance of the luminaire under different projection distances

GU10 7W LED Lamp

Technical Parameters

	Parameter	Unit	Nom	Max	Min
Electrical characteristics	1 Rated Wattage	w		7.7	6.3
	2 Rated Voltage	V/HZ	AC 220-240V 50/60HZ	240	100
	3 Power Factor		0.6		
	4 Driver Input current	mA	130mA 120V 80mA 230V	=	.
Photoelectric Parameter	5 Luminous flux [im]	lm	630	-	
	6 Lumen efficiency(Rated)	lm/W	91.46	-	
	7 Type and number LED	pcs	2835 7 PCS	8	
	8 Beam angle		60	65	55
	9 3000hours Lumen Maintenance	%	92	Ξ	
	10 CCT	к	Option	6500	2700
	11 Colour rendering index (Ra)		≥80	-	80
Other	12 Rated life(L70)	hrs	25000		
	Diameter 13	mm	50mm	51	49
	Height H	mm	56mm	57	55
	14 Hole size	mm		Ξ.	
	15 Base		GU10	-	
	16 Weight	9	33	2	
	17 Dielectric strength	V	4000	2	4000
	18 Electric shock proof grade				
	19 Dimmable (Y/N)				
	20 CE(Y/N)		¥		
	21 Work environment		-208 ~ +408, 10% ~ 80% R.H.		
	22 Storage environment		-208 ~ +508, 0% ~ 80% R.H.		
	23 Protection grade		IP20		
	24 Installation mode		Recessed		
		- C	-		

Indoor Light Distribution Curve