

GI FLEXIBLE CONDUIT (PVC COATED) PIPES



DESCRIPTION	Hot Dip Galvanized (for flexible conduit). Standard industrial conduit with galvanized sheet steel inner core and PVC over sheath. Helically wound with single clutch manufactured from galvanised steel metal with thin walled PVC over sheath.
APPLICATION	General Factory/plant rooms and connections to machines.
FLAMMABILITY	To CEI 23-14V - 1971 with 10 second flame resistance
PROTECTION RATING (IEC 529, IP 55)	Liquid: Protect against water jets. Water projected by a nozzle against the conduit from any direction will have no harmful effect. Dust: Dust protected. Ingress of dust is not totally prevented, but dust does not enter in sufficient quantity to interfere with the satisfactory operation of the equipment
STANDARDS	BS EN 50086 - 2 - 3 and BS 731 Part 1
MATERIAL	Steel (for flexible conduit) PVC (for cover)
STANDARD COLOUR	Black
SIZE	38 mm

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale

