

POLYCRYSTALLINE SILICON MODULE 200WP



Electrical Characteristics	
Module type	XJ200P
Pmax	200W
Tolerance	0-3W
Open-circuit Voltage (Voc)	44.22V
Short-circuit Current (Isc)	6.04A
Maximum Power Voltage (Vmp)	35.8V
Maximum Power Current (Imp)	5.59A
Maximum system voltage	1000 VDC
Maximum series fuse rating	15A
Temperature coefficient of Pmax	-0.41%/°C
Temperature coefficient of Voc	-0.33%/°C
Temperature coefficient of Isc	+0.03
Operating Temperature	-40~85°C



SCAN QR CODE

Mechanical Characteristics	
Dimension (mm)	1200*992*35mm
Weight (kg)	14.5kg
Number of cells	72(12x6)
Junction Box	IP67 rated
Output Cables	4mm ² , length: 900mm
Connector	MC4 compatible
Frame	Anodized Aluminium Alloy
Front Glass	3.2mm, low iron, tempered glass

METSEC

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale



SCAN QR CODE