

# PVC CLEAR BRAIDED HOSE



**Construction:**

Tube and Cover: PVC

**Application:**

PVC transparent hose is used for conveying water, oil, gas under normal working condition in factories, farm, ship, building and family.

**Characteristic:**

- Flexible, light, transparent
- Food grade, non-toxic, without odor
- Anti-erosion and anti-abrasion
- Anti-aging, long working life

**Temperature:**

-10°C (-50 °F) to 65°C (+150 °F)

Item Code	I.D		O.D	Thickness	Working Pressure		Burst Pressure		Length
	inch	mm	mm	mm	psi	bar	psi	bar	m
HCAMHOSCLBA040A>	3/16"								50
HCAMHOSCLBA060A>	1/4"	6	10	2	145	10	435	30	50
HCAMHOSCLBA080A>	5/16"	8	12	2	145	10	435	30	50
HCAMHOSCLBA100A>	3/8"	10	13	1.5	131	9	392	27	30
HCAMHOSCLBA100B>	3/8"	10	13	1.5	131	9	392	27	50
HCAMHOSCLBA120A>	1/2"	12	16	2	102	7	305	21	15
HCAMHOSCLBA120B>	1/2"	12	16	2	102	7	305	21	30
HCAMHOSCLBA120C>	1/2"	12	16	2	102	7	305	21	50
HCAMHOSCLBA200A>	3/4"	19	23	2	58	4	174	12	15
HCAMHOSCLBA200B>	3/4"	19	23	2	58	4	174	12	30
HCAMHOSCLBA200C>	3/4"	19	23	2	58	4	174	12	50
HCAMHOSCLBA250A>	1"	25	30	2.5	58	4	174	12	15
HCAMHOSCLBA250B>	1"	25	30	2.5	58	4	174	12	30
HCAMHOSCLBA250C>	1"	25	30	2.5	58	4	174	12	50
HCAMHOSCLBA320A>	1 1/4"	32	39	3.5	58	4	174	12	15
HCAMHOSCLBA320B>	1 1/4"	32	39	3.5	58	4	174	12	30
HCAMHOSCLBA320C>	1 1/4"	32	39	3.5	58	4	174	12	50

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale