

NITRILE HOSE



Description

Lightweight, flexible tubing with superb resistance to aliphatic hydrocarbons, good resistance to aromatic solvents and alcohols. Low gas permeability rate. Used in fuel installations, gas and lubricant lines and for petrochemical products transfer. Average resistance to ageing and light.

Material: Nitrile PVC

Max. Working Temperature: +70°C

Brittle Temp Hardness: -20°C

Key Features: 65° Shore (A)

Density: 1.45 g/cm³

Item code	I.D. [Inch]	O.D. [mm]	Wall thickness [mm]	working pressure [bar]	Bending Radius [mm]	Standard length [m]
HCAMHOSDELA120A>	1/2	17	2.5	0.54	68	30
HCAMHOSDELA200A>	3/4	28	4.5			30
HCAMHOSDELA200B>	3/4	28	4.5			Loose
HCAMHOSDELA250A>	1	36	5.3			30

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale