

PVC CLEAR HOSE



Construction:

Tube: PVC

Application:

PVC transparent hose is used for conveying water, oil, gas under normal working condition in factories, farm, ship, building and family.

Characteristic:

- Flexible, light, transparent
- Food grade, non-toxic, without odor
- Anti-erosion and anti-abrasion
- Anti-aging, long working life

Temperature : -10°C (-50 °F) to 65 °C (+150 °F)

| Item Code | I.D | | O.D | Thickness | Working Pressure | | Burst Pressure | | Length | |
|------------------|--------|----|-----|-----------|------------------|-----|----------------|-----|--------|-----|
| | inch | mm | | | mm | mm | psi | bar | | psi |
| HCAMHOSTBCA030A> | 1/8" | | | | | | | | | 50 |
| HCAMHOSTBCA040A> | 3/16" | | | | | | | | | 50 |
| HCAMHOSTBCA060A> | 1/4" | 6 | 8 | 1 | 21.75 | 1.5 | 65.3 | 4.5 | | 50 |
| HCAMHOSTBCA080A> | 5/16" | 8 | 10 | 1 | 21.75 | 1.5 | 65.3 | 4.5 | | 50 |
| HCAMHOSTBCA100A> | 3/8" | 10 | 12 | 1 | 21.75 | 1.5 | 65.3 | 4.5 | | 30 |
| HCAMHOSTBCA100B> | 3/8" | 10 | 12 | 1 | 21.75 | 1.5 | 65.3 | 4.5 | | 50 |
| HCAMHOSCLRA120A> | 1/2" | 12 | 15 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 15 |
| HCAMHOSCLRA120B> | 1/2" | 12 | 15 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 18 |
| HCAMHOSCLRA120C> | 1/2" | 12 | 15 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 30 |
| HCAMHOSCLRA120D> | 1/2" | 12 | 15 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 36 |
| HCAMHOSTBCA120A> | 1/2" | 12 | 15 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 50 |
| HCAMHOSTBCA120B> | 1/2" | 12 | 15 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 18 |
| HCAMHOSCLRA200A> | 3/4" | 19 | 22 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 15 |
| HCAMHOSCLRA200B> | 3/4" | 19 | 22 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 18 |
| HCAMHOSCLRA200C> | 3/4" | 19 | 22 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 30 |
| HCAMHOSCLRA200D> | 3/4" | 19 | 22 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 36 |
| HCAMHOSTBCA200A> | 3/4" | 19 | 22 | 1.5 | 14.5 | 1 | 43.5 | 3 | | 50 |
| HCAMHOSCLRA250B> | 1" | 25 | 30 | 2.5 | 14.5 | 1 | 43.5 | 3 | | 18 |
| HCAMHOSCLRA250C> | 1" | 25 | 30 | 2.5 | 14.5 | 1 | 43.5 | 3 | | 30 |
| HCAMHOSCLRA250D> | 1" | 25 | 30 | 2.5 | 14.5 | 1 | 43.5 | 3 | | 36 |
| HCAMHOSTBCA250A> | 1" | 25 | 30 | 2.5 | 14.5 | 1 | 43.5 | 3 | | 50 |
| HCAMHOSCLRA370C> | 1 1/4" | 32 | 38 | 3 | 14.5 | 1 | 43.5 | 3 | | 30 |
| HCAMHOSCLRA430C> | 1 1/2" | 38 | 44 | 3 | 14.5 | 1 | 43.5 | 3 | | 30 |

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale