

# PVC OXYGEN HOSE



**Construction:**

**Tube:** PVC material

**Reinforcement:** 1ply high tensile polyester braiding

**Cover:** PVC, black, blue.

**Application:**

Being widely used in welding machine, architecture and lacquer factory.

**Characteristics:**

- High tensile polyester reinforced
- Work under high pressure 300psi
- Strong peeling adhesion between fibre and PVC
- Light, flexible, non-kinking, on-twisting
- UV and ozone resistant, weather resistant.
- Can be used for jackhammer hose.

**Temperature:** -10°C (-50°F) to 65 °C (+150°F)

Item Code	I.D		O.D	Thickness	Working Pressure		Burst Pressure		Length
	inch	mm	mm	mm	psi	bar	psi	bar	m
	1/4"	6	12	3	300	20	900	60	
<b>HCAMHOSWLD0X08A&gt;</b>	5/16"	8	14	3	300	20	900	60	30
<b>HCAMHOSWLD0X08B&gt;</b>	5/16"	8	14	3	300	20	900	60	50
	3/8"	10	16	3	300	20	900	60	

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale