

## NETWORK PATCHCORD S/FTP Cat. 6A LSZH, grey.



### FEATURES:

<ul style="list-style-type: none"> <li>• Perfect connection</li> </ul>	<ul style="list-style-type: none"> <li>• Patch cord with foil shielded pairs and braided cable, CAT 6A</li> </ul>
<ul style="list-style-type: none"> <li>• Dual shielded for a reliable connection</li> </ul>	<ul style="list-style-type: none"> <li>• Gold plated contacts</li> </ul>
<ul style="list-style-type: none"> <li>• Low Smoke Zero Halogen (LSZH) jacket</li> </ul>	<ul style="list-style-type: none"> <li>• Low Smoke Zero Halogen (LSZH) jacket</li> </ul>
<ul style="list-style-type: none"> <li>• Gold plated contacts</li> </ul>	<ul style="list-style-type: none"> <li>• Molded strain reliefs</li> </ul>
	<ul style="list-style-type: none"> <li>• Snag less boots</li> </ul>

### Specifications

- Patch cord category 6A S/FTP (shielded) Length: according to the item
- Structure: AWG 27 (7 x 0.135 mm wire), COPPER FM-PE insulation of the wire: 1.0 mm
- With LDPE filler with polyester tape with aluminum foil
- Drain hose: not used
- With Braid: 16 x 4/0.12mm Outer insulation: 5.8 mm Color: according to the item Operation up to 250 MHz

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale



SCAN QR CODE