



## Fiber Optic Patch Cord, OM4, LC duplex to LC duplex, 1.8 mm LSZH, Aqua



Product Classification	
Product Type	Fiber patch cord, duplex

General Specifications	
Color, boot A	Blue
Color, boot B	Blue
Color, connector A	Beige
Color, connector B	Beige
Connector A, quantity	2
Connector B, quantity	2
Interface, Connector A	LC/UPC
Interface, Connector B	LC/UPC
Jacket Color	Aqua
Polarity	Pairs, flipped
Total Fibers, quantity	2

Dimensions		
	Diameter Over Jacket	1.8 mm   0.071 in

## **Mechanical Specifications**







Cable Retention Strength, maximum 11.24 lb @ 0 °

<b>Optical Specifications</b>		
Fiber Mode	Multimode	
Fiber Type	OM4, LazrSPEED®	
Insertion Loss, maximum	0.15 dB	
Return Loss, minimum	35 dB	

<b>Environmental Specifications</b>	
Operating Temperature	-10 °C to +60 °C (+14 °F to +140 °F)
Environmental Space	Low Smoke Zero Halogen (LSZH)
Qualification Standards	IEC 60332-1   IEC 60332-3   IEC 60754   IEC 61034

Packaging and Weights	
Packaging quantity	1

All of the above information, including drawings, illustrations and graphic designs, reflects our present understanding and is to the best of our knowledge and belief correct reliable. Users, however, should independently evaluate the suitability of each product for the desired application. Under no circumstances does this constitute an assurance any particular quality or performance. Such an assurance is only provided in the context of our product specifications or explicit contractual arrangements. Our liability for products set forth our standard terms and conditions of sale

