




**ecoFIT Tee 90° equal PE100**  
d20-500mm / SDR11

**Model:**

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100



d	DN	PN	SDR	FM	Code	Weight	L	L1	e
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)
20	15	16	11	IR	<b>753 208 606</b>	0.013	38	17	1.9
25	20	16	11	IR	<b>753 208 607</b>	0.021	42	17	2.3
32	25	16	11	IR	<b>753 208 608</b>	0.042	46	17	2.9
40	32	16	11	IR	<b>753 208 609</b>	0.065	51	22	3.7
50	40	16	11	IR	<b>753 208 610</b>	0.111	58	22	4.6
63	50	16	11	IR	<b>753 208 611</b>	0.202	66	21	5.8
75	65	16	11	IR	<b>753 208 612</b>	0.312	75	20	6.8
90	80	16	11	IR	<b>753 208 613</b>	0.553	90	20	8.2
110	100	16	11	IR	<b>753 208 614</b>	1.002	110	20	10.0
125	100	16	11	IR	<b>753 208 615</b>	1.509	125	25	11.4
140	125	16	11	IR	<b>753 208 616</b>	2.105	140	28	12.7
160	150	16	11	IR	<b>753 208 617</b>	3.085	160	28	14.6
180	150	16	11	IR	<b>753 208 618</b>	5.740	214	94	16.4
200	200	16	11	IR	<b>753 208 619</b>	5.982	200	35	18.2
225	200	16	11	IR	<b>753 208 620</b>	8.090	220	35	20.5
250	250	16	11		<b>753 208 621</b>	10.770	225	68	22.7
280	250	16	11		<b>753 208 622</b>	15.950	265	87	25.4
315	300	16	11		<b>753 208 623</b>	21.285	285	88	28.6
355	350	16	11		<b>753 208 624</b>	32.600	345	105	32.3
400	400	16	11		<b>753 208 625</b>	42.900	365	105	36.4
450	450	16	11		<b>753 208 626</b>	63.300	425	135	40.9
500	500	16	11		<b>753 208 627</b>	86.000	470	155	45.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>