


ECOS 160 - 250 - 315
Butt fusion machine for construction site

Butt Fusion machine to joint PE, PP, PB pipes and fittings for pressure piping systems on building sites and in trenches.
 Hydraulically operated with manual control unit.
 Temperature controller integrated in the heating element handle.
 Including transport packaging (carton pallet); reduction clamping inserts and other accessories to be ordered separately.

- **BASE MACHINE**
- High precision design, distortion-free and sturdy machine frame
- Good accessibility thanks to 35° inclination
- The movable (sliding) 3rd clamp allows easy and time-saving fixation of bends or tees without need of additional tools
- Clamps are hinged on the top side and tilting. Whenever necessary, the four clamps can be quickly removed
- Double-sided heating element pull-off mechanism to optimise the change-over phase
- Weight: Type 160 = 22 kg, Type 250 = 47 kg, Type 315 = 53 kg
- **HYDRAULIC UNIT**
- Compact construction with protection frame
- Precise pressure setting and fine adjusting
- Joystick operation of machine carriage
- Clearly visible, vibration-free pressure gauge with precision scaling
- Accumulator for pressure equalization during the cooling phase
- Integrated interface for welding recorder
- Max operating pressure: Type 160 = 100 bar, Type 250 - 315 = 160 bar
- Weight: 22 kg
- **PLANER**
- Powerful parallel planer for single or double-sided facing of pipe ends
- Ergonomic, weight-balanced handling
- Self-locking mechanism in working position
- Safety microswitch to prevent undesired start-up
- Weight: Type 160 = 7 kg, Type 250 = 14 kg, Type 315 = 17 kg
- **HEATING ELEMENT**
- High performance, electronically controlled heating element
- High-quality, non-stick PTFE-coating with long service life
- Temperature indicator integrated into the handle
- Weight: Type 160 = 5.5 kg, Type 250 = 8 kg, Type 315 = 10 kg
- Input power: Type 160 = 1200 W, Type 250 = 2000 W, Type 315 = 2500 W
- **CASE**
- For safe storage of planer and heating element
- Weight: Type 160 = 4.8 kg, Type 250 = 8 kg, Type 315 = 9 kg



Type	d-d (mm)	Performance	Description	Code	Weight (kg)
ECOS 160	40 - 160	230 V/1900 W	Without crate (carton pallet only)	790 150 009	78.000
ECOS 250	75 - 250	230 V/3270 W	Without crate (carton pallet only)	790 151 013	116.000
ECOS 315	90 - 315	230 V/3870 W	Without crate (carton pallet only)	790 152 028	129.000
ECOS 160	40 - 160	230 V/1900 W	With wooden transport crate	790 150 073	108.000
ECOS 250	75 - 250	230 V/3270 W	With wooden transport crate	790 151 073	166.000
ECOS 315	90 - 315	230 V/3870 W	With wooden transport crate	790 152 073	179.000

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>