




## 90° Elbow with threaded female off take

- Connection to plastic or metal threads
- with stainless steel reinforcement ring (**AISI430**)
- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- gasket: EPDM quality for drinkable water
- material: PP
- female thread: ISO 7 (parallel)
- colour: blue-black



d (mm)	Rp (inch)	PN (bar)	Code	SP	GP	Weight (kg)	D (mm)	L (mm)	l1 (mm)	l2 (mm)	l3 (mm)	H (mm)
16	½	16	<b>158 400 360</b>	10	50	0.061	45	67	54	19	15	40
20	½	16	<b>158 400 022</b>	10	180	0.046	45	67	54	19	15	40
20	¾	16	<b>158 400 023</b>	10	0	0.053	45	67	54	19	16	40
25	½	16	<b>158 400 024</b>	10	150	0.067	53	75	59	21	15	40
25	¾	16	<b>158 400 025</b>	10	150	0.071	53	75	59	21	16	44
25	1	16	<b>158 400 026</b>	10	120	0.081	53	75	59	21	16	44
32	½	16	<b>158 400 027</b>	10	110	0.099	64	87	66	23	15	43
32	¾	16	<b>158 400 028</b>	10	110	0.110	64	87	66	23	16	46
32	1	16	<b>158 400 029</b>	10	0	0.121	64	87	66	23	20	54
32	1 ¼	16	<b>158 400 030</b>	10	90	0.131	64	87	66	23	22	57
40	¾	16	<b>158 400 031</b>	70		0.159	75	102	76	26	16	49
40	1	16	<b>158 400 032</b>	70		0.176	75	102	76	26	20	57
40	1 ¼	16	<b>158 400 033</b>	70	0	0.191	75	102	76	26	22	62
40	1 ½	16	<b>158 400 034</b>	50		0.200	75	102	76	26	22	63
50	1	16	<b>158 400 035</b>	30		0.303	97	119	88	30	20	61
50	1 ¼	16	<b>158 400 036</b>	30		0.324	97	119	88	30	22	66
50	1 ½	16	<b>158 400 037</b>	30		0.335	97	119	88	30	22	70
50	2	16	<b>158 400 038</b>	30		0.371	97	119	88	30	26	75
63	1 ¼	16	<b>158 400 039</b>	15	0	0.537	114	144	104	35	22	73
63	1 ½	16	<b>158 400 040</b>	15	0	0.561	114	144	104	35	22	76
63	2	16	<b>158 400 041</b>	15	0	0.604	114	144	104	35	26	83
75	2	16	<b>158 400 042</b>	12		0.949	135	180	133	41	26	91
75	2 ½	16	<b>158 400 043</b>	12		1.003	135	180	133	41	31	101
75	3	10	<b>158 400 044</b>	10		1.112	135	180	133	41	34	108
90	3	10	<b>158 400 045</b>	6		1.615	161	207	150	44	34	116
110	4	10	<b>158 400 046</b>	3		2.474	185	242	175	53	40	135

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>