




90° Tee

- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- material: PP
- gasket: EPDM quality for drinkable water
- colour: blue-black




d (mm)	PN (bar)	Code	PF	SP	GP	Weight (kg)	D (mm)	L (mm)	l1 (mm)	l2 (mm)	H (mm)
16	16	158 400 354	2 85 A07 020	10	30	0.160	45	134	46	19	67
20	16	158 400 223	2 85 A07 001	10	100	0.098	45	134	54	19	67
25	16	158 400 224	2 85 A07 001	10	70	0.147	53	150	59	21	75
32	16	158 400 225	2 85 A07 001	10	40	0.238	64	173	66	23	87
40	16	158 400 226	2 85 A07 001	30		0.391	75	203	76	26	87
50	16	158 400 227	2 85 A07 001	12		0.753	97	239	88	30	119
63	16	158 400 228	2 85 A07 001	8		1.203	114	288	104	35	144
75	16	158 400 229	2 85 A07 001	5		2.207	135	360	133	41	180
90	16	158 400 230	2 85 A07 001	2		3.596	161	413	150	44	207
110	16	158 400 231	2 85 A07 001	1		5.342	185	484	175	53	242

PF 2 85 A07 001

90° Reducing-Increasing Tee

- installation without disassembling
- suitable for PE and PEX pipes
- water PN16
- material: PP
- gasket: EPDM quality for drinkable water
- colour: blue-black



d-d-d (mm)	PN (bar)	Code	SP	GP	Weight (kg)
20 - 25 - 20	16	158 400 200	10	70	0.100
25 - 20 - 25	16	158 400 232	10	70	0.133
25 - 32 - 25	16	158 400 201	10	50	0.181
32 - 25 - 32	16	158 400 233	10	40	0.213
40 - 32 - 40	16	158 400 234	30		0.348
50 - 32 - 50	16	158 400 235	15		0.596
50 - 40 - 50	16	158 400 236	12		0.643
63 - 32 - 63	16	158 400 237	8		0.948
63 - 50 - 63	16	158 400 238	8		1.076
75 - 63 - 75	16	158 400 239	5		1.915
90 - 75 - 90	16	158 400 240	2		3.196
110 - 63 - 110	16	158 400 241	1		4.148
110 - 90 - 110	16	158 400 242	1		4.865

d-d-d (mm)	d (mm)	d1 (mm)	D (mm)	D1 (mm)	L (mm)	l1 (mm)	l2 (mm)	l4 (mm)	l3 (mm)	H (mm)
20 - 25 - 20	20	25	45	53	134	54	19	59	21	81
25 - 20 - 25	25	20	53	45	150	59	21	54	19	71
25 - 32 - 25	25	32	53	64	150	59	21	66	23	93
32 - 25 - 32	32	25	64	53	173	66	23	59	21	81
40 - 32 - 40	40	32	75	64	203	76	26	66	23	93
50 - 32 - 50	50	32	97	64	239	88	30	66	23	99
50 - 40 - 50	50	40	97	75	239	88	30	76	26	109
63 - 32 - 63	63	32	114	64	288	104	35	66	23	108
63 - 50 - 63	63	50	114	97	288	104	35	88	30	129
75 - 63 - 75	75	63	135	114	360	133	41	104	35	157
90 - 75 - 90	90	75	161	135	413	150	44	133	41	196
110 - 63 - 110	110	63	185	144	484	175	53	104	35	182
110 - 90 - 110	110	90	185	161	484	175	53	150	44	224